



**POLYPROPYLENE
COMPOUNDED RESINS**

SPECIALTY RESINS AND COMPOUNDS

**AAROLENE® ARPP 200 SERIES
COMPOUNDED RESINS
ARPP200-2 PP BLACK COPOLYMER HIGH FLOW**

	PROPERTIES	ASTM METHOD	UNITS OF MEASURE	C 200-2
GENERAL	SPECIFIC GRAVITY	D-792	g/cm ³	.900
	MOLD SHRINKAGE	D-955	in/in	.022
MECHANICAL	TENSILE STRENGTH @ Yield	D-638	PSI	3700
	FLEXURAL MODULUS	D-790	PSI	180,000
	IZOD IMPACT @ 73° (Notched)	D-256	ft-lbs./in.	2.0
THERMAL	MELT FLOW INDEX (230/2.16)	D-1238	g/10 min	30
	DEFLECTION TEMPERATURE	D-648	°F @ 66PSI	220

FEATURES: A high flow Polypropylene Copolymer Resin pre-colored black specifically designed for all high speed injection molding applications.

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions concerning uses or applications are only the opinion of Aaron Ind. Corp. and users should perform their own tests to determine the suitability of these products for their own particular purposes. However, because of numerous factors affecting results, Aaron Ind. Corp. MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MANUFACTURING AND FITNESS FOR PURPOSE, other than that the material conforms to the applicable current Standard Specifications Statements herein.